

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1209)

Set a sandstone 24x16x6 ins. 18" in the ground for cor. to secs. 22, 23, 26 and 27, marked with 2 notches on S. and E. edges, and raised a mound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12891-92)

The Sec. cor., monumented with a sandstone boulder, 28x14x6 ins., firmly set, 20" in the ground, with faint notches visible on S. and E. edges.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T 21 S R 11 W
S 22 S 23
S 27 S 26
1960

from which

A Fir 8" dia., bears N.21½°E., 13 lks. dist. mkd. T21S R11W S23 BT.

A Fir 15" dia., bears S.35°E., 7 lks. dist. mkd. T21S R11W S26 BT.

A Fir 13" dia., bears S.87°W., 12 lks. dist. mkd. T21S R11W S27 BT.

A Fir 10" dia., bears N.13°W., 26 lks. dist. mkd. T21S R11W S22 BT.

Deposit the original corner stone alongside the iron post.

Survey by Ronald E. Stuntzner, LS #1342 - For: International Paper Co. and Siuslaw National Forest - May 1980 - M 84-51

Found - 2½" brass cap set in 1960 by BLM, properly mkd.

10" D.Fir bears N.13°W., 17.2 ft.

Blown down D.Fir BTs in NW, SW, and SE quadrants.

New BTs -10" D.Fir bears N.22°E., 21.7 ft.

26" Maple bears S.48°E., 110.0 ft. with scribed bark.

No acceptable witness monuments in SW quadrant.

Survey by James W. Prochnau, LS #1305 - For: U.S. Forest Service - Feb. 24, 1984 - M 96-62; C.S. File 58/294 and M 96-61 A&B

----- (Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found - 1960 BLM brass cap.
BLM BT, a 14" D.Fir bears N.13°W., 17.2 ft., healed face.
Stuntzner BT, a 10" D.Fir bears N.22°E., 21.7 ft. healed face.
Stuntzner BT, a 26" Maple bears S.48°E., 110.0 ft.
Set 3" alum. cap on 2½" x 30" alum. pipe reference monument bears N.55°56'51"E., 48.55 ft. mkd. "RM S22 S23 S27 S26 1984 PLS 1305 48.55", with arrow pointing to corner.