TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 23

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1209)

Set a sandstone 15x10x6 ins. 10 in the ground for ¼ sec. cor. marked ¼ on W. face, from which
A Fir 36" dia., bears S.34½°W., 36 lks. dist. mkd. ¼ S BT
A Fir 36" dia., bears N.77°E., 10 lks. dist. mkd. ¼ S BT.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12893)

The ¼ sec. cor. of secs. 22 and 23, determined at record bearing and distance from each of the original bearing trees:
A Fir 50" dia., bears N.77°E., 10 lks. dist. with no marks remaining on scaled off bark blaze.
A sawed Fir stump 53" dia., bears S.34½°W., 36 lks. dist. with scribe marks ¼ S BT visible on bark.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

¼
S 22 S 23
T 21 S R 11 W
1961

from which
A Fir 50" dia., bears N.77°E., 10 lks. dist. mkd. ¼ S23 BT. (This is the original NE. tree, remarked because no other tree is available.
An Alder 18" dia., bears N.29°W., 75 lks. dist. mkd. ¼ S11 BT.