TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for secs. 14 and 15

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1207)

Set a post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which
A Fir 24" dia., bears S.63½°W., 592 lks. dist. mkd. ¼ S BT
A Fir 40" dia., bears S.60½°E., 555 lks. dist. mkd. ¼ S BT

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12896)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: ¼
S15 S14
T 21 S R 11 W
1960
from which
A Maple 23" dia., bears S.88°E., 64 lks. dist. mkd. ¼ S14 BT.
A Maple 35" dia., bears S.29½°W., 59 lks. dist. mkd. ¼ S15 BT.

Survey by Eugene Wobbe - International Paper Co. - May 1987 -M 104-43 A&B

Found - A Brass cap and accessories of record.
A Maple bears S.29½°W., 59 lks.
Scribed -A 10" Cherry bears S.53°E., 5.7 ft.

Found and used in BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19596)