

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1204)

Set a sandstone 24x12x3 ins., 18" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which

A Cedar 12" dia., bears N.3½°W., 37 lks. dist. mkd. ¼ S BT

A Cedar 16' dia., bears S.71°E., 84 lks. dist. mkd. ¼ S BT

Survey by Bruce A. Shaner RLS #430 - For: Moore Mill & Lumber Co. - March/July 1981 - RM 3-48

Found - 24" x 12" x 6" sandstone.

30" W.Red Cedar (orig. BT) marked face visible, no scribes, bears N.3½°W., 24.4 ft.

36" W.Red Cedar stamp (orig. BT) marked face vis. no scribes, bears S.63°E., 54.0 ft. (Rec. S.71°E., 55.4 ft.)

Set Brass cap marked "T21S R11W WM ¼ S10 S11 RLS 430 1981"

Original sandstone reset alongside.

New BTs -12" D.Fir, I scribed ¼ S10 BT, bears West 93.1 ft.

8" W.Red Cedar, I scribed ¼ S11 BT, bears N.12°E., 84.0 ft.

Survey by Eugene Wobbe - For: International Paper Co. - May 1987 - M 104-43 A&B

Found - Brass cap and accessories of record.

32" Cedar bears N.3½°W., 24.4 ft.

38" Cedar stump bears S.63°E., 54.0 ft. (Rec. S.71°E., 55.4 ft.)

16" Fir bears West, 93.1 ft.

10" Cedar bears N.12°E., 84.0 ft.

Fd. Ok L Roberts, 2/1990 - C.S. File 63/126-9