

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1163-64)

-----  
Set post for cor. to secs. 2, 3, 10 and 11, from which  
An Alder 8" dia., bears N.55°E., 65 lks. dist.  
An Alder 3" dia., bears N.43°W., 11 lks. dist.  
A Fir 24" dia., bears S.38°E., 100 lks. dist.  
A Fir 20" dia., bears S.71°W., 40 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1203)

-----  
Fire having destroyed the cor. to secs. 2, 3, 10 and 11.  
Set a sandstone 24x18x4 ins., 18" in the ground for cor. to secs. 2, 3, 10 and 11 mkd. 5 notches on S. and 2 notches on E. edges, and raised a mound of stone 1½ ft. high, 2 ft. base alongside; pits impracticable.

Survey by Bruce A. Shaner - For: Moore Mill & Lumber Co. - July 1981 - RM 3-48

-----  
Set Brass cap mkd. "T21S R11W WM S2 S3 S10 S11 RLS 430 1981".  
BTs - 10" D.Fir, I scribed "T21S R11W S11 BT", bears S.63°E., 46.0 ft.  
12" D.Fir, I scribed "T21S R11W S2 BT", bears N.24°E., 11.5 ft.  
24" D.Fir, I scribed "T21S R11W S10 BT", bears S.63°W., 66.6 ft.  
No trees near in Sec. 3.

Fd. OK, Nov. 1990 - M 111-10 & C.S. 63/126-11