

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1210)

-----  
Set a sandstone 10x10x6 ins., 7" in the ground for ¼ sec. cor., mkd. ¼ on N. face, and raised a mound of stone, 1½ ft. high and 2 ft. base alongside, pits impracticable.

Survey by Wilford Haines - For: Cone Lumber - Aug. 1974 - M 54-33

-----  
Found location poster N.06°E., 194.0 ft. No bearing or distance on poster.  
Set 5/8" steel rod temp. 1/4 S23 and 26.

Survey by Ronald E. Stuntzner - For: International Paper Co. and Siuslaw National Forest - May 1980 - M 84-51

-----  
Found - 5/8" Iron rod bears S.42½°W., 215.0 ft. set in survey for Cone Lumber Co. dated Aug. 19, 1974. Thoroughly searched for original corner stone and was not found, therefore set this corner at proportional distance. Set 2½" x 36" alum. capped alum. pipe mkd. "T21S R11W 1/4 S23 S26 1980 PLS 1342".  
New BTs -20" D.Fir bears N.45°W., 18.0 ft.  
24" D.Fir bears S.12°E., 73.6 ft.

Survey by James W. Prochnau, LS #1305 - For: U.S. Forest Service - Feb. 24, 1980 - M 96-62; C.S. File 58/294 and M 96-61

-----  
Found - 3" alum. cap on 2½" alum. pipe set by Stuntzner.  
21" D.Fir stump bears N.45°W., 18.0 ft. visible scribe.  
24" D.Fir bears S.12°E., 73.6 ft. visible scribe.  
Set reference monument, a 2½" brass cap on a 1" iron pipe bears S.35°48'45"E., 47.25 ft. mkd. "R.M. 47.25 1/4 S26 1984 PLS 1305" with arrow pointing to corner.