

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1208)

Set a sandstone 9x8x7 ins. 6" in the ground, for ¼ sec. cor. mkd. ¼ on N. face, and raised a mound of stone 1½ ft. high and 2 ft. base alongside; pits impracticable.

BLM resurvey by Floyd A. Brooks, Cadastral Surveyor, under Group #430, Surveyed June/Aug 1960 (DCSO records Vol. 31 Page(s) 12895)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 12" long, 1" dia., 6" in drill hole, in sandstone ledge, with brass cap mkd: ¼ S 14

S 23

T 21 S R 11 W

1960

from which

A Cedar 12" dia., bears N.44½°W., 12 lks. dist. mkd. ¼ S14
BT.

A Fir 18" dia., bears S.73½°E., 21 lks. dist. mkd. ¼ S23
BT.