

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1206)

-----  
Set a post 3 ft. long, 3" sq., 18" in the ground for ¼ sec.cor. marked ¼ S on N. face, from which

A Chittum 8" dia., bears S.75½°W., 46 lks. dist. mkd. ¼ S BT.

A Cherry 6" dia., bears N.68°W., 29 lks. dist. mkd. ¼ S BT

Survey by Ronald Stuntzner - For: International Paper Co. - Dec. 1979 - M 81-43

-----  
No evidence of original corner found. Set by proportionate distance.

Set 2" x 36" brass cap with iron pipe stamped "PLS 1342 1/4 S11|S14 1979", from which

8" Chittum bears N.65°W., 14.7 ft.

10" D.Fir bears S.76°E., 12.4 ft.

Survey by Les Roberts, LS #1039 - For: International Paper Co.- Nov. 20, 1990 - C.S. File 63/126-1 and M 111-10

-----  
Found - 2" x 36" Iron pipe with brass cap as set in survey M 81-43.

BTs - 9" Cascara N.53°W., 14.1 ft., bark scribed, 1979 BT.  
(Rec. N.65°W., 14.7 ft.)

15" Fir S.82°E., 12.3 ft. bark scribed, 1979 BT.  
(Rec. S.76°E., 12.4 ft.)