

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 563200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1238)

Set a sandstone 15x10x5 ins., 10" in the ground mkd. C C on N. face, and notch on S. and E. edges for closing cor. to secs. 35 and 36, and raised a mound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

Survey by James W. Prochnau, LS #1305 - For: U.S. Forest Service - Feb.1984 - M 96-61 A&B; M 96-62 and C.S. File 58/294

Set 2" alum. cap on 24" x 1/2" Iron rod in sandstone. Cap stamped per BLM Manual and with "PLS 1305". Rock mound.
New BTs -16" D.Fir bears S.3°E., 25.1 ft. scribed T21S R1W
S36 CC BT.
12" D.Fir bears S.59°W., 23.5 ft. scribed T21S R11W
S35 CC BT.