

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 600114

PRIMARY CORNER DESCRIPTION M.C. bet. secs. 35 and 36

Alias <u>891020</u>	Description <u>M.C. right bank of Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1237)

-----  
The meander post on right bank of Umpqua River, bet. fractional secs. 35 and 36, being a Willow, 4" dia., mkd. MC on S. face, T21S on N. face, R11W S36 on E. face, S35 on W. face, from which

- A Willow 6" dia., bears N.32°E., 26 lks. dist. mkd. T21S R11W S36 MC BT.
- A Willow 6" dia., bears N.10°W., 24 lks. dist. mkd. T21S R11W S35 MC BT.

Frank Cain - Sept. 27, 1912 - Field Book 61 Pg. 41

-----  
Set a Cedar post 4"x4"x4 ft. long, marked MC CS on S. face; T21S on N. face; R11W S36 on E. face; and S35 on W. face, from which

- A Spruce 28" dia., bears N.42°20'W., 108½ lks. mkd. MC S35 CS BT.
- An Ader 12" dia., bears N.73°15'E., 24 lks. mkd. MC S36 CS BT.

Survey by James W. Prochnau, PLS #1305 - For: U.S. Forest Service - June 1985 - M 98-79 A&B

-----  
Found - 2½" I.P. with screw cap by Byars orig. M.C. as found by Lecklinder in 1958.

Set 3" alum. cap mkd. T21S R11W S35 S36 MC 1985 PLS 1305, on 2½" alum. pipe filled with concrete.

New BTs -16" Alder bears N.16°W., 53.5 ft. scribed T21S R11W S35 MC BT.

11" Alder bears N.10°E., 63.6 ft. scribed T21S R11W S36 MC BT.

(Note: In research of materials given to me for corner project, I could find no material by Byars.) V.Laugen, Nov. 1995