

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1238)

Set a sandstone 12x10x5 ins. in the ground for ¼ sec.cor. marked ¼ on W. face, and raised a mound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

Survey by James W. Prochanu - For: U.S. Forest Service - June 1985 - M 98-79 A&B

Found - 2" Iron pipe 3 ft. out of ground, set by Lewis (PE 722 1939)

Lewis BT, 15", 4 ft. high snag stump, bears S.30°W., 1.5 ft. visible scribe.

Lewis BT, 32" D.Fir bears N.40°E., 10.5 ft. with healed face.

Set 3" alum. cap mkd. T21S R11W 1/4 S35 S36 1985 PLS 1305, on 2½" alum. pipe. Rock mound.

New Bearing Object:

Reference monument, a 3" alum. cap on 2½" alum. pipe, bears S.24°13'47"W., 53.88 ft. mkd. "RM 1/4 S35 S36 1985 PLS 1305 53.88", with arrow pointing to corner.