

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1201)

Set a sandstone 9x9x7 ins. 6" in the ground for cor. to secs. 23, 24, 25 and 26 marked 2 notches on S. and 1 notch on E. edge; raised a mound of stone 1½ ft. high, 2 ft. base alongside; pits impracticable.

Survey by Ronald E. Stuntzner LS #1342 - For: International Paper Co. and Siuslaw National Forest - May 1980 - M 84-51

Found - Orig. sandstone corner monument. One scribe groove mark visible.
1968 20" D.Fir stump with alum. poster nails as per U.S.F.S. corner perpetuation notes. Scribes now burned with chop marks visible.

Set 2½" x 36" alum. capped alum. pipe mkd. "T21S R11W S23 S24 S25 S26 1980 PLS 1342."

New Accessories:

24" D.Fir stump bears N.50°E., 2.5 ft. Sction 24 BT.
30" D.Fir stump bears S.44°E., 12.3 ft. Sec. 25 BT.
Mkd. "X" in rock face bears N.72°W., 36.3 ft.
Mkd. "X" in rock bluff bears S.6°W., 14.0 ft.