

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1199)

Set a sandstone 11x10x5 ins. 8" in the ground for cor. to secs. 13, 14, 23 and 24, marked with 3 notches on S. and 1 notch on E. edges; and raised a mound of stone, 1½ ft. high, and 2 ft. base, alongside; pits impracticable.

BLM resurvey by Thomas A. Tillman, Civil Engineer (Cadastral), under Group #373, under Special Instructions dated Aug. 6, 1957 - (DCSO records Vol. 29 Page(s) 12334)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 30" long, 2½" dia., 2" in the ground to bedrock in a mound of stone, 6 ft. base, to top, with brass cap mkd:

T21S R11W
S 14 S 13
S 23 S 24
1957

from which

- A Fir 50" dia., bears N.42°E., 46 lks. dist. mkd. T21S R11W S13 BT.
- A Maple 10" dia., bears S.40°E., 41 lks. dist. mkd. T21S R11W S24 BT.
- A Fir 50" dia., bears S.58½°W., 48 lks. dist. mkd. T21S R11W S23 BT.
- A Fir 20" dia., bears N.74°W., 100 lks. dist. mkd. T21S R11W S14 BT.

The sec. cor. is located 10 lks. E. of a ravine, course SE., at base of a sandstone ledge, 5 ft. high, faces S.

Cor. Fd. and used in BLM resurvey by F. Brooks under Group #430, surveyed June/Aug. 1960 (DCSO records, Vol. 31 Pg. 12894)

Survey by Richard J. Hintz, LS 497 - For: Siuslaw National Forest - July 1986 - M 102-19

Found - 12" Maple bears S.40°E., 27.8 ft. (Rec. 17.1 ft.) with closed face.

40" sawed D.Fir stump bears S.56°W., 30.5 ft. (Rec. S.58½°W., 31.7 ft.) with closed face.

20" sawed D.Fir stump bears N.75°W., 65.3 ft. (rec. N.74°W., 66.0 ft.) with closed face.

NE BT is missing. (No new tree accessible.)

(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set 5/8" x 20" Iron rod with 3½" USDA FS alum. cap driven 10" into bedrock mkd. "T21S R11W 14, 13, 23, 24 1986 P.L.S. 497" Bearing Object:

Set 5/8" x 16" Iron rod with 3¼" USDA-F.S. Alum. cap drilled 6" into a rock outcrop and mkd. "T21S R.M., R11W N.73°44'E 40.8' S23 1986 PLS 497".