

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1199)

Set a sandstone 10x10x6 ins., 7" in the ground for ¼ sec.cor. mkd. ¼ on W. face, and raised a mound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

BLM resurvey by Thomas A. Tillman, Civil Engineer (Cadastral), under Group #373, under Special Instructions dated Aug. 6, 1957 - (DCSO records Vol. 29 Page(s) 12336)

Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30" long, 2½" dia., 26" in the ground, with brass cap mkd:
T21S R11W
¼
S 14 S 13
1957

from which

A Fir 58" dia., bears S.28°E., 54 lks. dist. mkd. ¼ S13 BT
A Fir 62" dia., bears S.19½°W., 47 lks. dist. mkd. ¼ S14 BT.

Survey by Richard J. Hintz - For: Siuslaw National Forest - July 1986 - M 102-19

Found - A 2½" Iron pipe with brass cap (BLM 1957).
60" D.Fir bears S.28°E., 35.6 ft. closed face.
66" D.Fir bears S.19°W., 30.0 ft. (Rec. S.19½°W., 31.0 ft.) with closed face.

Set bearing object:

A 2½" x 30" alum. pipe with a ¾" USDA - F.S. alum. cap stamped "R.M. N.84°59'W 1/4 - S13 48.8', 1986 P.L.S. 497"