

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1198)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on North face, from which
 An Alder 3" dia., bears S.29°E., 47 lks. dist. mkd. ¼ S BT
 A Vinemaple 3" dia., bears N.45°W., 27 lks. dist. mkd. ¼ S BT.

Survey by Robert G. Kintigh - For: Tree Farm Management - July 1960 - C.S. File 51/106

At a point midway on the S. line of sec. 12, the bearing and distance of which is 2643.8 ft., S.85°57'E., of the sec. cor. for secs. 11, 12, 13 and 14, I set the S. ¼ corner. This corner is mkd. with a 1" x 45" galv. iron pipe 25" in the ground and surrounded by a mound of native stone.
Two BTs as follows:
 22" crooked gr. D.Fir bears N.43°15'E., 44.6 ft. scribed S12 BT.
 42" gr. D.Fir bears S.70°30'W., 74.4 ft. to center of tree and scribed S13 BT on face looking at the corner.

Survey by Richard Hintz - For: International Paper Co. - Nov. 1983 - M 95-40

Set 1¼" x 36" I.P. with stamped brass cap PLS 497 1983.
BTs - 14" Alder bears S.24°30'W., 10.5 ft.
 8" Hemlock bears N.83°30'W., 20.9 ft.
Both trees scribed.
(1" I.P. from C.S. 51/106 bears N.33°58'E., 91.95 ft.)