

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 640540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Ronald E. Stuntzner - For: International Paper Co.
- Feb. 3, 1984 - M 96-23

Set 3/4" x 30" I.R. with 2" alum. cap stamped with PLS 1342
and as prescribed, at the intersection of the E-W and N-S
center lines of the section.

New BTs -14" Alder bears S.58°W., 13.9 ft., I scribed.
12" Alder bears N.46°E., 27.8 ft., I scribed.
50" Cedar bears S.10°E., 59.0 ft. Not scribed.

Gary Smithers - Aug 2005 - C.S. File 65/54-30

Found - 1984 2" Alum cap on 3/4" IR firmly set. We set a 6
ft galvanized steel post alongside the monument
58" Cedar S.10°E., 59.0 ft. not scribed, we place
new tag.

14" Alder Snag S.58°W., 13.9 ft., with visible bark
scribe and tag.

9" Alder Snag N.46°E., 27.8 ft., with visible bark
scribe, we place new tag.

New BTs- 25" Maple, N.18°E., 62.8 to spike driven in side
center, Scribed "T21 R11 C¼ S12 BT", with BT tag.