

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 700162

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only, T21-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1051-52)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for
¼ sec. cor. of sec. 31 only, with brass cap mkd: ¼
S31
1919

from which

A Maple 12" dia., bears N.80°E., 50 lks. dist. mkd. ¼ S31
BT.

A Maple 12" dia., bears S.71°E., 138 lks. dist. mkd. ¼ S31
BT.

Survey by James W. Prochnau PLS #1305 - For: U.S. Forest Service - Aug. 1985 - M 99-21 A & B

Found - A 1" x 30" Iron post set by GLO in 1919 at corner
position. Cap has been broken off. Buried pipe.
38" Maple bears N.80°E., 33 ft., no marks.

Set a U.S. Forest Service 3¼" alum. cap with magnet, on a 2½"
x 30" alum. flared pipe, mkd: "T21S R11W R10W ¼ S31 1985 PLS
1305". Rock mound.

New BTs -12" Maple, bears N.67°E., 88.5 ft. scribed ¼ S31 BT
18" Maple bears S.19°E., 49.1 ft. scribed ¼ S31 BT.