TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1191)

Set a sandstone 14x7x6 ins., 10" in the ground, marked with 4 notches on N. and 2 notches on S. edges, for cor. to secs. 24, 25, 19 and 30; and raised amound of stone, 1½ ft. high and 2 ft. base alongside; pits impracticable.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1054)

Apportioned distance
Set an iron post 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 24 and 25, with brass cap mkd:

T21S
S24
S25
R11W
1919

from which
A Fir 12" dia., bears S.63°W., 15 lks. dist. mkd. T21S R11W S25 BT.
A Fir 10" dia., bears N.87°W., 17 lks. dist. mkd. T21S R11W S24 BT.