

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1190)

-----  
Set a sandstone 12x8x6 ins., 9" in the ground for ¼ sec. cor. mkd. ¼ on W. face, and raised a mound of stone 1½ ft. high, 2 ft. base, alongside. Pits impracticable.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1055)

-----  
Apportioned distance  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor. of sec. 24 only, with brass cap mkd:  
S24 |  
1919

from which  
A Fir 26" dia., bears S.59°W., 176 lks. dist. mkd. ¼ S24 BT.  
A Fir 6" dia., bears N.58°W., 37 lks. dist. mkd. ¼ S24 BT

Reported as NF by DCSO 7/1968 C.S. 54/1-16A