

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 700411

PRIMARY CORNER DESCRIPTION W. Sec. cor. for 18 & 19 only, T21-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1056)

-----  
Set an iron post 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 18 and 19, with brass cap mkd:  
T21S  
S 18  
S 19  
R10W  
1919

from which  
A Fir 36" dia., bears N.27°E., 76 lks. dist. mkd. T21S R10W S18 BT.  
A Hemlock 24" dia., bears S.83°E., 21 lks. dist. mkd. T21S R10W S19 BT.

Survey by Herman Pieske, PLS 1651 - For: U.S. Forest Service - Nov. 1984 - M 97-77 A & B

-----  
Found - 1919 GLO brass cap properly marked.  
60" D.Fir bears N.27°E., 50.2 ft. healed face.  
30" Hemlock bears S.75°E., 13.9 ft. healed face.  
(Rec. S.83°E.)  
Set 2½" x 30" alum. pipe flush in 18" mound of stone with ¾" cap mkd. "USDA Forest Service T21S R10W R11W S18 S19 RLS 1651 1984".