

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1189)

A Fir 4" dia., which I marked ¼ S on W. side, for ¼ sec. cor., from which

A Fir 24" dia., bears East, 12 lks. dist. mkd. ¼ S BT.

A Fir 3" dia., bears S.75°W., 8 lks. dist. mkd. ¼ S BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 1057)

Apportioned distance

Set an iron post 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor. of sec. 13 only, with brass cap mkd:

¼
S 13
1919

from which

A Hemlock 8" dia., bears S.70°W., 12 lks. dist. ¼ S13 BT"

A Fir 18" dia., bears N.65°W., 6 lks. dist. mkd. ¼ S13 BT.

BLM resurvey by Thomas A. Tillman, Civil Engineer (Cadastral), under Group #373, under Special Instructions dated Aug. 6, 1957 - (DCSO records Vol. 29 Page(s) 12338)

At the ¼ sec. cor. of sec. 13 only, on the E. bdy. of the tsp., which is monumented with an iron pipe, 1" dia., 6" above ground, firmly set, from which

A dead Fir 20" dia., bears N.65°W., 6 lks. dist. with partial scribe marks visible on nearly healed blaze.

A Hemlock 12" dia., bears S.70°W., 12 lks. dist. with partial scribe marks visible on opened blaze.

Build a mound of stone 2½ ft. base, to top of an iron post, and mark a new bearing tree, as follows:

A Hemlock 10" dia., bears N.2 3/4°W., 48 lks. dist. mkd. ¼ S13 BT.

Survey by Herman Pieske, RLS 1651 - For: U.S. Forest Service - Nov. 1984 - M 97-77 A&B

Found - 1½" I.P. with 1919 GLO brass cap.

12" Hemlock bears S.70°W., 7.8 ft. visible scribed "S" in partially healed face.

14" Hemlock bears N.2½°W., 31.7 ft. chopped open face visible "BT".

Fir snag, now badly rotted, bears N.65°W., 4.0 ft.

(Cont. Next Page)

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set 2½" x 30" alum. pipe 3" above ground with mound of stone with ¾" alum. cap mkd. "USDA Forest Service T21S R10W R11W ¼ S13 RLS 1651 1984 Unlawful to Disturb".

Survey by Richard Hintz, PLS 497 - For: Siuslaw National Forest - July 1986 - M 102-19

Found - ¾" USDA Forest Service alum. cap.
12" Hemlock bears S.70°W., 7.8 ft. (7.9 ft. rec.)
partially closed face visible.
18" D.Fir snag bears N.65°W., 4.0 ft.
14" hemlock bears N.2½°W., 31.7 ft. opened face,
visible "BT".

Set 2½" x 30" alum. pipe with ¾" USDA F.S. alum. cap mkd.
"R.M. T21S R10W S1°26'W, 40.7' ↓ S18 1986 P.L.S. 497".