

TOWNSHIP 21 RANGE 11 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 1; & S. 6, T21-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 3 Page(s) 1168)

Set post for ¼ sec. cor., from which
A Maple 12" dia., bears N.70°W., 11 lks. dist.
A Cedar 7" dia., bears S.10°E., 55 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1186)

The ¼ sec. cor. on the E. bdy. of Sec. 1, which is a post, badly decayed, 4" sq., 24" above ground, mkd. ¼ S on W. face, from which
A Maple 12" dia., bears N.70°W., 11 lks. dist. mkd. ¼ S BT
A Cedar 7" dia., bears S.10°E., 55 lks. dist. mkd. ¼ S BT.

Survey by Herman Pieske, LS 1651 - For: U.S. Forest Service Nov. 1984 - M 97-76 A&B

At proper position, Set 2½" x 30" alum. pipe 28" in the ground, with 3¼" alum. cap mkd: "USDA Forest Service T21S R10W R11W ¼ S1 S6 1984 RLS 1651 Unlawful to Disturb".
New BTs -36" Hemlock bears N.19°E., 84.8 ft. scribed "¼ S6 BT" in double blaze.
27" Cedar bears N.57°E., 67.2 ft. scribed "¼ S6 BT" in double blaze.
32" Cedar bears N.1°W., 48.6 ft. scribed "¼ S1 BT"