

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 037090

PRIMARY CORNER DESCRIPTION SW Cor. Addison Gibbs DLC #37

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DLC survey by Harvey Gordon Deputy Surveyor, under Contract #89 dated 1858

On right bank of Umpqua River, Set post, from which
An Alder 6" dia., bears S.59°E., 32 lks.
An Alder 6" dia., bears N.57°E., 65 lks.

Found among F. Cain's notes by M.C. Bowker in Sept. 24, 1926 (no record source, see "old" corner book, Vol. 1 Page 16

Set a Fir post 4" square firmly in the ground and properly marked, from which
An Alder 6" (12") dia., bears S.59°E., 32 lks. dist.
An Alder 12" dia., bears N.58°E., 44 lks. dist.

Douglas County Surveyors Office - F.L. Ingram and John Powell, crew - Jan. 1972 - C.S. File 56/7-5

Corner found by field crew, not of record.
This point 5/8" Iron rod flush with concrete, in driveway on the East side of Highway No. 101. No trace of Alder BTs as mentioned above.
(Note: G. Langlitz in 1974, C.S. File 57/12-5?, felt that this report mistakenly dealt with the wrong corner.)