

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 039040

PRIMARY CORNER DESCRIPTION Most W. NW. cor. Scholfield DLC 39


Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO DLC survey by Socrates Scholfield, Deputy Surveyor, under Contract dated March 31, 1859

-----  
Set stake, from which  
A Spruce 12" dia., bears South, 36 lks.  
A Spruce 30" dia., bears S.89°W., 45 lks.  
A Fir 30" dia., bears N.49°E., 10 lks.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17123)

-----  
Point for the NW. cor. of DLC #39, determined by the Grant Boundary Method; there is no remaining evidence of the original corner.  
Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:



from which  
A Fir 15" dia., bears N.74°E., 46½ lks. dist. mkd. DLC 39  
BT.  
A Fir 27" dia., bears N.75°W., 9 lks. dist. mkd. DLC 39  
BT.

Fd. OK, Jan/March 1982 by Clayton Martin - M 91-61

Douglas Co. Surveyors Office - SJF & JL - 6/19/2019 - C.S. 67/46-4

-----  
Found - Brass Cap, 2 BTs & carsonite posts.  
Carsonite posts bear:  
N.35°E., 4.4'  
South 4.4'  
New BT tags.