TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 039060

PRIMARY CORNER DESCRIPTION Int. Cor. on So. bdy. DLC #39

Alias Description
Alias Description
Alias Description
Alias Description

GLO DLC Survey by Socrates Scholfield, Deputy Surveyor, under Contract dated March 31, 1859

Set stake for corner, from which
A Spruce 60" dia., bears N.15°E., 53 lks.
A Spruce 15" dia., bears N.59°E., 64 lks.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17211-12)

The interior cor. on the S. bdy. of DLC #39, perpetuated by person(s) unknown, monumented with an iron rod, 1" dia., firmly set, projecting 4" above ground, from which the remains of the original bearing trees:
A sawed Spruce stump 60" dia., bears N.15°E., 53 lks. dist. with decayed blaze, no marks visible.
A decayed Spruce stump 15" dia., bears N.59°E., 54 lks. dist., no marks visible.
At the corner point
Set an alum. post, 28" long, 2½" dia., 22" in the ground, directly over the iron rod, with alum. cap mkd:

DLC 39
/\
/ \
/ \
/ S 17 \
1981

from which new bearing trees
A Spruce 16" dia., bears N.3°E., 53½ lks. dist. mkd. DLC 39 BT.
A Spruce 30" dia., bears S.5¼°W., 31 lks. dist. mkd. S17 DLC 39 BT.

Fd. OK, Jan/Mar. 1982 by Clayton Martin - M 91-61

Found OK by R. Ward, June 2001 - 2002-0048