

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 039070

PRIMARY CORNER DESCRIPTION Ext. Cor. on So. bdy. DLC #39

Alias <u>841440</u>	Description <u>M.C. right bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO DLC survey by Socrates Scholfield, Deputy Surveyor under Contract dated March 31, 1859

Set corner stake, from which
A Fir 18" dia., bears S.73°W., 10 lks.
A Fir 30" dia., bears N.59°E., 10 lks.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17211)

The exterior cor. on the S. bdy. of DLC #39 on the right bank of the Umpqua River, determined from the original bearing trees:

A Fir 44" dia., bears N.59°E., 10 lks. dist. with scribe mark D visible on partially healed blaze.
A Fir 30" dia., bears S.73°W., 10 lks. dist., with healed blaze.

At the corner point
Set an alum. rod, 4 ft. long, 5/8" dia., 3½ ft. in the ground, with alum. cap mkd:



The corner is located on the right bank of the Umpqua River, bears N.70°E. and S.40°W.