

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1301)

-----  
Set ¼ sec. post, from which  
A Pine 10" dia., bears N.10°W., 112 lks. dist.  
No tree convenient South of line.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17210)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:  
T 21 S R 12 W  
1/4  $\frac{S\ 19}{S\ 30}$   
1981

from which  
A Fir 10" dia., bears N.47°E., 37 lks. dist. mkd. ¼ S19 BT  
A Pine 16" dia., bears S.41½°E., 35 lks. dist. mkd. ¼ S30 BT.

The corner is located at top of ascent, slopes S.