

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1301)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.40°W., 430 lks. dist.
A Fir 10" dia., bears (omitted)

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17201)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:

T 21 S R 12 W

1/4 $\frac{S \ 18}{S \ 19}$
1981

from which

A Pine 10" dia., bears S.46°E., 9 lks. dist. mkd. ¼ S19 BT

A Pine 10" dia., bears N.7°W., 38 lks. dist. mkd. ¼ S18 BT