

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 158300

PRIMARY CORNER DESCRIPTION M.C. on So. bdy. Sec. 19

Alias <u>841650</u>	Description <u>M.C. on right bank Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1301-02)

Right bank of Umpqua River.
Set post, from which
A Pine 18" dia., bears N.48½°W., 605 lks. dist.
No tree convenient S. of line.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17210-11)

Point for the meander cor., on the right bank of the Umpqua River, at record distance; there is no remaining evidence of the original corner.
Set an alum. post, 28" long, 2½" di., 23" in the ground, in concrete, with alum. cap mkd:
T 21 S R 12 W
S 19 \ MC
S 30 \
1981

No suitable trees available within limits.
Set a steel fence post alongside alum. post.
The corner is located in low lying dunes, 5.40 chs. West of the right bank of the Umpqua River, which bears N.10°W. and S.10°E.
From this point, United States Coast and Geodetic Survey triangulation station "BRUSHY HILL 2", bears N.39°28'W., 23.46 chs. dist., monumented with a standard brass tablet 3½" dia., set in drill hole in exposed bedrock, with top mkd. BRUSHY HILL 2 1928 and a triangle.