

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 200371

PRIMARY CORNER DESCRIPTION M.C. on East bdy. Sec. 19

Alias 841540 Description M.C. on right bank of Umpqua River  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1302)

-----  
Right bank of Umpqua River  
Set post, raised a monument of stones.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17199-200)

-----  
(7.54 chs.)  
Point selected for the witness cor. to the meander cor. of secs. 19 and 20, on the right bank of the Umpqua River.  
Set an alum. rod, 4 ft. long, 3/4" dia., 3½ ft. in the ground, and in a collar of stone, with alum. cap mkd:

WC  
T 21 S R 12 W  
S 19 S 20  
↓/  
/ MC  
1981

from which

A Spruce 5" dia., bears N.76°E., 22½ lks. dist. mkd. X BT.  
An XBO chiseled on a sandstone bluff 12 ft. high, bears S.80°W., 49½ lks. dist.

The corner is located on the right bank of the Umpqua River, which bears N.40°E. and S.40°W.

(9.00 chs.)

True point for the meander cor. of secs. 19 and 20, on the right bank of the Umpqua River, at record distance; there is no remaining evidence of the original corner. This point falls in the tide plain of the river, where it is impracticable to establish a permanent monument.