

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1300)

Set ¼ sec. post, from which
A Spruce 12" dia., bears S.23°W., 25 lks. dist.
An Alder 6" dia., bears N.23°E., 10 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17203)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, with alum. cap mkd:
T 21 S R 12 W
1/4
S 18 S 17
1981

from which
A Pine 12" dia., bears East, 97½ lks. dist. mkd. ¼ S17 BT
A Pine 15" dia., bears N.18°W., 18 lks. dist. mkd. ¼ S18 BT.