

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1291)

- 
- Set post cor. of secs. 7, 8, 17 and 18, from which
- A Hemlock 12" dia., bears N.30°W., 8 lks. dist.
  - A Hemlock 24" dia., bears S.68°E., 88 lks. dist.
  - A Spruce 36" dia., bears S.52½°W., 42 lks. dist.
  - A Spruce 30" dia., bears N.6°E., 50 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17204)

-----

The sec. cor., determined from the remains of the original bearing trees:

- A sawed Spruce stump, 30" dia., bears N.6°E., 52 lks. dist., no marks visible. (Rec. 50 lks.)
- A decayed Hemlock stump 24" dia., bears S.68°E., 89½ lks. dist., no marks visible. (Rec. 88 lks.)
- A sawed Spruce stump 36" dia., bears S.52½°W., 44 lks. dist., no marks visible. (Rec. 42 lks.)
- A root hole bears N.30°W., 8 lks. dist. with a down and decayed Hemlock alongside, 12" dia., no marks visible.

At the corner point

Set an aluminum post 28" long, 2½" dia., 22" in the ground, with alum. cap mkd:

T 21 S	R 12 W
<u>S 7</u>	<u>S 8</u>
S 18	S 17

1981

from which new bearing trees

- A Spruce 15" dia., bears N.63½°E., 24 lks. dist. mkd. T21S R12W S8 BT.
- A Spruce 15" dia., bears S.18°E., 8½ lks. dist. mkd. T21S R12W S17 BT.
- A Spruce 24" dia., bears S.85°W., 43 lks. dist. mkd. T21S R12W S18 BT.
- A Spruce 12" dia., bears N.54°W., 23 lks. dist. mkd. T21S R12W S7 BT.