

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1298)

-----  
Set ¼ sec. post, from which  
A Spruce 60" dia., bears N.52°E., 30 lks. dist.  
A Spruce 10" dia., bears N.84°W., 14 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17206-07)

-----  
The ¼ sec. cor. of secs. 7 and 8, determined from the remains of the original bearing trees:

A decayed Spruce stump 60" dia., bears N.52°E., 34 lks. dist. with opened blaze, no marks visible. (Record and to face, 30 lks.)

A decayed Spruce stump 36" dia., bears N.84°W., 16 lks. dist. with opened blaze, no marks visible. (Record and to face, 14 lks.)

At the corner point

Set an aluminum post 28" long, 2½" dia., 22" in the ground with aluminum cap mkd:

T 21 S R 12 W  
1/4  
S 7 S 8  
1981

from which new bearing trees

A Spruce 25" dia., bears North 23½ lks. dist. mkd. ¼ S7 BT.

A Spruce 8" dia., bears S.20°E., 54½ lks. dist. mkd. ¼ S8 BT.