

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1298)

- 
- Set post cor. of secs. 5, 6, 7 and 8, from which
- A Spruce 24" dia., bears N.27°W., 13 lks. dist.
  - A Spruce 30" dia., bears S.67°W., 37 lks. dist.
  - A Spruce 36" dia., bears S.72°E., 19 lks. dist.
  - A Spruce 18" dia., bears N.55°E., 22 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17207-08)

-----

The sec. cor., determined from the remains of the original bearing trees:

- A root hole bears N.55°E., 22 lks. dist.
- A decayed Spruce stump 70" dia., bears S.72°E., 23½ lks. dist., no marks visible. (Rec. 19 lks.)
- A decayed Spruce stump 67" dia., bears S.67°W., 41 lks. dist., no marks visible. (Rec. 37 lks.)
- A root hole bears N.27°W., 13 lks. dist.

At the corner point

Set an aluminum post 28" long, 2½" dia., 22" in the ground, with alum. cap mkd:

T 21 S R 12 W  
S 6 S 5  
S 7 S 8  
1981

from which new bearing trees

- A Spruce 12" dia., bears N.21½°E., 18½ lks. dist. mkd. T21S R12W S5 BT.
- A Spruce 20" dia., bears S.23°E., 41 lks. dist. mkd. T21S R12W S8 BT.
- A Spruce 12" dia., bears S.11°W., 57 lks. dist. mkd. T21S R12W S7 BT.
- A Spruce 12" dia., bears N.10°W., 46 lks. dist. mkd. T21S R12W S6 BT.