

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1299)

Set ¼ sec. post, from which  
A Hemlock 12" dia., bears N.37°E., 45 lks. dist.  
A Spruce 6" dia., bears S.74°W., 60 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17209)

The ¼ sec. cor. of secs. 5 and 6, perpetuated by person(s) unknown, monumented with an iron pipe, 1½" dia., firmly set, projecting 4" above the ground, from which the remains of an original bearing tree:

A decayed Hemlock stump 20" dia., bears N.37°E., 45 lks. dist. with scribe mark B visible on open blaze.

At the corner point

Set an alum. post 28" long, 2½" dia., 20" in the ground, directly over the iron pipe, with alum. cap mkd:

T 21 S R 12 W  
1/4  
S 6 S 5  
1981

from which new bearing trees

A Spruce 15" dia., bears N.26°E., 3 lks. dist. mkd. ¼ S5 BT.

A Spruce 22" dia., bears N.44°W., 10 lks. dist. mkd. ¼ S6 BT.