

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T20-12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 8)

Set post corner of secs. 5, 6, 31 and 32, from which
A Spruce 40" dia., bears S.3°E., 21 lks. dist.
A Spruce 15" dia., bears N.82°W., 50 lks. dist.
A Spruce 36" dia., bears S.72°W., 58 lks. dist.
An Alder 12' dia., bears N.38°E., 40 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17194)

Point for the cor. of secs. 5, 6, 31 and 32, at record distance; there is no remaining evidence of the original corner.

Set an alum. post, 28" long, 2½" dia., 23" in the ground, with alum. cap mkd.

T 20 S R 12 W
S 31 S 32
S 6 S 5
T 21 S
1981

from which

- A Spruce 32" dia., bears N.59°E., 75½ lks. dist. mkd. T20S R12W S32 BT.
- A Spruce 22" dia., bears S.16°E., 54½ lks. dist. mkd. T21S R12W S5 BT.
- A Spruce 19" dia., bears S.56°W., 37 lks. dist. mkd. T21S R12W S6 BT.
- A Spruce 17" dia., bears N.27°W., 17½ lks. dist. mkd. T20S R12W S31 BT.

Fd. and used in BLM resurvey by Goodson, Tawney and Acuna, under Group #1077, surveyed Sept. 1981/Oct. 1982 (DCSO records, Vol. 44 Pages 17123-24)