

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 208400

PRIMARY CORNER DESCRIPTION M.C. on So. bdy. Sec. 17

Alias <u>841530</u>	Description <u>M.C. on right bank of Umpqua River</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1302)

Right bank of Umpqua River.

A Pine 6" dia., is meander cor. from which

A Pine 6" dia., bears N.65°W., 36 lks. dist.

A Fir 12" dia., bears S.62°W., 20 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17200)

(7.85 chs.)

Point selected for the witness cor. to the meander cor. of secs. 17 and 20, on the right bank of the Umpqua River.

Set an alum. rod, 4 ft. long, 3/4" dia., 3½ ft. in the ground, with alum. cap mkd: WC

T 21 S R 12 W

S 17 / MC
S 20 /

1981

from which

A Fir 7" dia., bears N.34°E., 64 lks. dist. mkd. X BT.

A Fir 7" dia., bears S.56°W., 31 lks. dist. mkd. X BT.

Set a steel fence post alongside alum. post.

(8.00 chs.)

True point for the meander cor. of secs. 17 and 20 on the right bank of the Umpqua River, at record distance; there is no remaining evidence of the original corner. This point is located in the tidal path of the Umpqua River, where it is impractical to establish a permanent monument.