

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 218100

PRIMARY CORNER DESCRIPTION M.C. on S. bdy. Sec. 32

Alias 844080 Description M.C. on Left bank Umpqua River
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1262)

Set meander post on left bank of Umpqua River, from which
A Spruce 48" dia., bears N.30°W., 30 lks. dist.
A Spruce 48" dia., bears S.45°E., 30 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17185-86)

At the meander cor. of secs. 5 and 32, on the left bank of the Umpqua River, determined at record bearing and distance from the remains of an original bearing tree;

A sawed and decayed Spruce stump, 60" dia., bears N.30°W., 30 lks. dist. with remains of an old blazed face, no marks visible.

Set an alum. post 28" long, 2½" dia., 24" in the ground, with alum. cap mkd:

T 21 S R 12 W
MC S 32
S 5
T 22 S
1981

from which

A Spruce 30" dia., bears S.59¼°E., 13 lks. dist. mkd. T22S R12W S5 MC BT.

A Spruce 11" dia., bears N.2°W., 58½ lks. dist. mkd. T21S R12W S32 MC BT.

The corner is located on the left bank of Umpqua River, bears N. and S., course S.