

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1299)

-----  
Set ¼ sec. post, from which  
An Alder 8" dia., bears S.15°W., 36 lks. dist.  
An Alder 10" dia., bears N.8°E., 55 lks. dist.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17208)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an alum. post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:  
T 21 S R 12 W  
1/4  $\frac{S}{S} \frac{5}{8}$   
1981

from which  
A Hemlock 30" dia., bears S.85½°E., 32 lks. dist. mkd. ¼ S8 BT.  
A Hemlock 13" dia., bears N.70°W., 19 lks. dist. mkd. ¼ S5 BT.