

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5; and 32, T20-12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 8)

Place of qr. sec. corner is on side of steep mountain.
(Wit. Cor. placed 4.50 chs. East)

Survey by W.G. Corbitt; H. Hendrickson - For: Crown Zellerback - Aug. 4, 1943 - C.S. File 52/91

At 2+97 West of wit. cor.,
Set 1½" I.P. and 2x2x4 Fir post, crayon mkd. "2+97 W of W.C. S32 S5 Aug. 4, 1943 by W.G. Corbitt".
from which bears,
8 ft. Fir N.65°W., 11.5 ft. crayon mkd. "RP 35 ft. W of
Creek course 5 W.
Field notes call for ridge SW at 23+10.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17193-94)

True point for the ¼ sec. cor. of secs. 5 and 32, at record distance from the original witness corner.
Set an alum. post, 28" long, 2½" dia., 24" in the ground, with alum. cap mkd. T 20 S R 12 W

1/4 $\frac{S\ 32}{S\ 5}$
T 21 S
1981

from which
A Fir 10" dia., bears S.81°E., 16½ lks. dist. mkd. ¼ S5 BT
A Fir 11" dia., bears N.0¼°W., 12½ lks. dist. mkd. ¼ S32 BT.

Fd. and used in BLM sec. subd. by Goodson, Tawney and Acuna, under Group #1077, surveyed Sept. 1981/Oct. 1982 - (DCSO records. Vol. 44 Pages 17160-61)