TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 300451

PRIMARY CORNER DESCRIPTION M.C. on West bdy. Sec. 16

Alias 841380 Description M.C. Right bank Umpqua River
Alias Description
Alias Description
Alias Description

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1295-96)

(26.60 chs.)
Bluff near right bank of Umpqua River
Set witness post, from which
An Alder 6" dia., bears N.1°W., 20 lks. dist.
An Alder 8" dia., bears N.46½°E., 14 lks. dist.
(29.60 chs.) (South)
To right bank of river, place of true meander cor.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17196-97)

(25.86 chs.)
Point selected for the witness cor. to the meander cor. of secs. 16 and 17, on the right bank of the Umpqua River.
Set a brass tablet, 3¼" dia., 3½" stem, in drill hole, in base of a sandstone clif, with top mkd. WC

T 21 S R 12 W
S 17 S 16
↓/
/
MC
1981

from which
An XBO, chiseled on sandstone cliff, 75 ft. high, bears N.58°E., 17 lks. dist.
An XBO chiseled on sandstone cliff, 75 ft. high, bears S.83°W., 8½ lks. dist.
The corner is located at base of sandstone cliff, 75 ft. high, bears N.60°E. and N.60°W., on right bank of the Umpqua River.
(29.60 chs.)
True point for the meander cor. of secs. 16 and 17, on the right bank of the Umpqua River, at record distance; there is no remaining evidence of the original corner. This point falls in the river, and is impossible to monument.