

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 17 and 18

Alias <u>039010</u>	Description <u>Pt. on NE bdy. Scholfield DLC #39</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1292)

-
- Set post cor. of secs. 8, 9, 16 and 17, from which
- A Spruce 18" dia., bears N.50°W., 2 lks. dist.
 - A Spruce 12" dia., bears S.14°W., 23 lks. dist.
 - A Spruce 18" dia., bears S.24°E., 38 lks. dist.
 - A Hemlock 12" dia., bears N.74°E., 10 lks. dist.

Douglas County Surveyors Office - Clell Goodwin, Deputy - Gary Langlitz; Vic Cangie; Lenora Ladig, crew - Feb. 3, 1976 C.S. File 59/2-14

Found approx. 30" Spruce with visible scribed "S" and "BT" identified by John Powell as having recognizable S16 when originally opened. The root wad on this tree is intact and appears to have come from a slight depression with roots at the base of this tree. From this location, we pull the call distance and bearing (N.24°W., 25.1 ft.) and locate a point which falls in roots from what may have been the original NW BT but cannot be identified. From this point, we chain West and find the edge of the called swamp at 2 chs. At this point, which we believe to be the proper location, we set a 1" x 30" I.P. with brass cap stamped: Douglas Co. Surveyor

T21 S	R12W
S 8	S 9
S 17	S 16
1976	

from which

- A 9" D.Fir scribed "T21S R12W S17 CS BT" in a double blaze bears S.55½°W., 6.0 ft.
- A 10" D.Fir scribed "T21S R12W S9 CS BT" in a double blaze bears N.28°E., 23.3 ft.

(Due to a lack of any other trees, we scribe the following additional tree in the NE. quadrant:)

- A 7" D.Fir scribed "T21S R12W CS BT 2" in a double blaze bears N.83½°E., 23.4 ft.

At the road crossing approx. 130 ft. West of the corner, we set a line crossing tag.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17195-96)

The sec. cor. perpetuated and recorded by Goodwin in 1976, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground with properly mkd. B.C. (Cont. Next Page)

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias <u>039010</u>	Description <u>Pt. on NE bdy Scholfield DLC #39</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees:
A decayed Spruce stump 24" dia., bears S.24°E., 38 lks. dist. with a down Spruce alongside, with scribe marks BT visible on partially open blaze.
A root hole, bears S.14°W., 23 lks. dist.
A root hole, bears N.50°W., 2 lks. dist. with a down Spruce alongside, 14" dia., no marks visible.
and bearing trees mkd. by Goodwin:
A Fir 15" dia., bears N.29¼°E., 35 lks. dist. with healed blaze.
A Fir 11" dia., bears N.83°E., 36 lks. dist. with healed blaze.
A Fir 12" dia., bears S.56¼°W., 9 lks. dist. with illegible scribe marks visible on partially healed blaze.
and a new bearing tree:
A Fir 5" dia., bears S.31°E., 6½ lks. dist. mkd. X BT.

Fd. B.C. and 3 BTs, Nov. 1992 by C. Mulkins - M 116-21
Fd. Ok by Jerry Estabrook, 6/2007 - 2007-0083A-E