

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1297)

-----  
Set ¼ sec. post, from which  
A Fir 12" dia., bears S.27°W., 27 lks. dist.  
An Alder 18" dia., bears N.27°W., 33 lks. dist.

Survey by W.G. Corbitt; H. Hendrikson - For: Crown Zellerbach August 5, 1943 - C.S. File 52/91

-----  
Found original BT bearing SW. which is dead Spruce snag, from it reset corner.  
Set 1½" I.P. and 2x2x5 ft. Spruce post, crayon mkd. "¼ S4 S9 Aug. 19 1943 W.G. Corbitt", from which bears  
Orig. 12" Fir now 25" Spruce snag 30 ft. high, S.27°W., 17.84 ft. to scribed face ¼ S or 17.6 ft. to nail.  
4 ft. Spruce S.38°15'E., 45.8 ft., crayon mkd. "RP BT S9"  
5 ft. Fir N.89°30'W., 24.7 ft., crayon mkd. "RP BT S4"  
Corner stands 17 ft. East of creek, course S. by E.

Fd. by Oreg. St. Hwy. Dept. in 1952 - (DCSO records, D-3)