

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 4; and 33 of T20-12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 1 Page(s) 7)

-----  
Set qr. sec. post, from which  
A Spruce 60" dia., bears S.75°E., 80 lks. dist.  
A Spruce 30" dia., bears N.67°E., 112 lks. dist.

Survey by W.G. Corbitt; H. Hendrickson - For: Crown Zellerbach Corp. - Aug. 21, 1943 - C.S. File 52/91

-----  
No BTs found, so set:  
Pipe at proportional distance between MC 33 and 4 and corner for 32, 33, 5 and 4.

Robert Ward, L.S. #1091 - For: Siuslaw National Forest & Tahkenitch Tree Farm Partnership - April 1995 - M 122-3 A

-----  
Found - Corbitt's 1½" I.P,  
REPLACED pipe with a 2½"x30" Alum.  
cap mkd: T20S R12W ¼ S33 S4 T21S 1994 LS 1091, from  
which  
BTs - 18" Spruce, bears N.45°E., 22.1 ft. (¼ S33 BT)  
30" D.Fir, bears S.50°E., 8.0 ft. (¼ S4 BT)  
10" Spruce, bears S.4°E., 19.4 ft. (X BT)  
10" Spruce, bears S.13 3/4°W., 13.6 ft. (¼ S4 BT)