

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 3 Page(s) 1284)

Set post cor. of secs. 27, 28, 33 and 34, from which
A Hemlock 18" dia., bears N.34°W., 18 lks. dist.
A Hemlock 18" dia., bears S.73°W., 37 lks. dist.
A Hemlock 24" dia., bears S.20°E., 62 lks. dist.
A Hemlock 20" dia., bears N.84°E., 93 lks. dist.

Douglas County Surveyors Office - F.L. Ingram and John M. Powell - Jan. 1972 - C.S. File 56/7-4

Corner found by field crew, not of record.
Found - 1 3/4" x 23" Axle, flush with ground.
Telephone pole near fence with yellow tag, S.36½°W.,
76.6 ft.
SE. corner of chimney, N.41°W., 162.3 ft.
This corner also tied to triangulation point, "SLIM".
International Paper Co. also set Iron Rods 1320 ft. East and
665 ft. (?) East of 1/16. Not too sure of line, more or less
an agreement line.

Survey by Richard J. Hintz - For: International Paper;
Menasha Corp. & U.S. Forest Service - Nov 1980 - M 84-24 A&B

Found - 1" I.R., 3" below ground, from which
SE corner of brick chimney bears N.40°45'W., 178.7
ft. formerly given as N.41°W., 162.3 ft.
50d nail on West side of pole AI 34 D bears
S.36°15'W., 75.9 ft. 1
formerly given as S.36°30'W., 76.6 ft.
Set steel fence post 1 ft. North of corner.

Survey by Daniel Baker - For: International Paper Co. - Dec.
15, 1986 - M 103-32

Found - 1" Iron rod, 4" below ground and under car.
SE corner of chimney, N.40 3/4°W., 178.8 ft.
Broken power pole, S.38°W., 76.0 ft. (Rec. per M 84-
24, S.36¼°W., 75.9 ft.)
Set spike in new power pole, AE 34D bears S.39°W., 61.1 ft.
1

Fd. Harvey Wilcox, 3/2000, Partition Plat 2000-0096
Fd. OK by G. Solarz, July 2003 - Partition Plat 2003-0053
Fd. OK by Matt Whitty, Jan 2007 2007-0018
Fd. Axle by M. Dado, Oct. 2010, 2010-0034

continued next page

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 8/21/2025 - C.S. File 67/61-19

Found - 1" Iron rod 2" below ground.
S.E. corner of chimney N.40¼°W. 178.8 ft
Spike in power pole AE34D S.39°W. 61.1 ft.
1
N.E. corner of steel clad barn S.52¼°W. 97.0 ft barn
is 99' N-S and 84' E-W.
5/8" iron rod with yellow plastic cap stamped "Wilcox
LS 2244" from L.P. 2000-0096 set flush with ground.
Notes - Mon on flat pasture ground 35'± north of gravel driveway.
Compass decl. 14½°E.
OGRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
43°42'42.49626 N.
124°07'28.36432 W.