

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec Cor for 9, 10, 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1292-93)

Set post cor. of secs. 9, 10, 15 and 16, from which
An Alder 18" dia., bears S.89°E., 35 lks. dist.
An Alder 24" dia., bears S.17½°W., 15 lks. dist.
An Alder 20" dia., bears N.87°W., 48 lks. dist.
A Fir 36" dia., bears N.32°E., 19 lks. dist.

Survey by Ben B. Irving, D.C.S. - Wit: N.E. Richardson and Loren Weber - July 18, 1940 - C.S. File 16/55

Location identified from an old Fir stake and BT.
Set a post 7" x 50" for corner, from which
A Fir 36" dia., bears S.5½°W., 87 ft. (slope). This tree had been previously marked but was not an original. Marked T21S R12W S15 CS BT.
A Fir 40" dia., bears S.59°E., 105.0 ft. (slope) marked T21S R12W S15 CS BT.
A Fir 50" dia., bears N.46°W., 60.5 ft. (slope) marked T21S R12W S10 CS BT. This tree had been previously marked.
A Fir 60" dia., bears N.32°E., 19 lks. This is an original BT and was remarked.

Douglas County Surveyors Office - Fritz Ingram, John M. Powell, J. Heritage, crew - Jan. 31, 1972 - C.S. File 56/7-1

Found - 40" D.Fir now stag, S.59°E., 105.0 ft. S.D. bark scribe visible "T21".
50" D.Fir now stump, N.46°W., 60.5 ft. S.D.
No trace of other BTs.

Set Brass cap at cor. mkd: County Surveyors Office

T 21 S R 12 W
S 9 | S 10
S 16 | S 15
1972

New BTs -10" Alder S.43°W., 11.6 ft. "T21S R12W S16 CS BT."
14" Alder N.75°W., 37.0 ft. "T21S R12W S9 CS BT."
6" Alder N.52½°E., 8.6 ft. "T21S R12W S10 CS BT."
8" Alder S.77°E., 12.0 ft. "T21S R12W S15 CS BT."

This corner lies on easterly edge of logging road.

Fd. OK, May 1, 1993 by R. Ward - M 117-9
FD Ok, 4/1/1996 by Clyde Mulkins, M 125-10
Fd. OK by T. Rambo, Sept. 2000 - M135-63