

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1279)

-----

Set post cor. of secs. 14, 15, 22 and 23, from which

- An Alder 9" dia., bears S.54°W., 9 lks. dist.
- An Alder 12" dia., bears S.21°E., 30 lks. dist.
- An Alder 14" dia., bears N.63°E., 8 lks. dist.
- A Spruce 14" dia., bears N.31°W., 48 lks. dist.

Ben B. Irving, D.C.S. - Wit: N.E. Richardson; Loren Weber - July 19, 1940 - C.S. File 16/55 (and "old" cor. book, Vol. 1 Page 16) and C.S. File 49/6

-----

Location identified from old stake and a BT, Fir 24" dia., S.42°W., scribed T21S R12W S22. The stake and tree are not original but were set approx. 35-40 years ago.

Set a 2½" x 2½" x 48" post for corner, from which

- A Fir 50" dia., bears S.82°W., 50 ft. "T21S R12W S22 CS BT"
- An Alder 15" dia., bears N.70°E., 23.4 ft. "T21S R12W S14 CS BT"
- An Alder 15" dia., bears S.33°E., 47.0 ft. "T21S R12W S23 CS BT"
- A Fir 60" dia., bears N.38°W., 32.3 ft. "T21S R12W S15 CS BT"

This location fits topography as records original field notes.

Survey by Tom McCullough - For: U.S. Forest Service - April 1970 - C.S. File 55/148-8

-----

Found 2½" x 2½" post set by Eppstein (?), scribing visible, from which,

- 26" Fir bears S.46°W., 40.0 ft., face pitched over. This BT is not an orig. according to Eppstein, it was scribed between 1890 and 1895, 4 notches and X scribed, with tags.
- 42" Fir snag bears N.28°W., 32.3 ft., face visible, axe marks, has 4 notches and X scribed in tree. Eppstein does not make reference to, but believe same as above.
- 62" Fir stump bears N.38°W., 32.3 ft. (cut low to ground)

No evidence of face set by Eppstein in 1929.

Set 2" x 30" I.P. with brass cap mkd. T21S R12W

14	14
22	23
1970	

from which  
(Cont. Next Page)

