

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1282)

Set ¼ sec. post, from which
 An Alder 14" dia., bears S.80°E., 12 lks. dist.
 A Fir 40" dia., bears S.86°W., 18 lks. dist.

Survey by Richard J. Hintz - For: Champion International and International Paper Co. - March 1980 - M 79-30 and C.S. File 58/140

Found - Orig. 40" Fir BT, stump.
Set 2" I.P. with stamped brass cap, from which
 10" Fir bears S.10°00'E., 16.0 ft., scribed.
 50" Fir stump bears S.86°00'W., 11.9 ft. Orig. BT.
 8" Fir bears N.29°00'W., 13.7 ft., scribed.

Clyde Mulkins, surveyed for: Port Blakely Tree Farms; Scott Timber Co.; Menasha Corp. July 1997 - M 127-39

Found - 2½" brass cap, from which:
 60" D.Fir stump with a burned out face, bears S.87°W., 10.9 ft. to the face.
 21" D.Fir, with a healed face, bears N.26°W., 14.0 ft.
 17" D.Fir, with a healed face, bears S.9°E., 16.2 ft.
New Accessories -
 14" Spruce, bears S.67°W., 13.5 ft. scribed "¼ S10 BT"
 14" Alder, bears N.77°E., 18.7 ft. scribed "¼ S11 BT"