

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1282)

Set post cor. of secs. 2, 3, 10 and 11, from which
An Alder 15" dia., bears S.55°E., 16 lks. dist.
An Alder 18" dia., bears N.62°E., 36 lks. dist.
An Alder 15" dia., bears N.74°W., 50 lks. dist.
A Spruce 70" dia., bears S.21°W., 52 lks. dist.

W.G. Corbitt; C. Boatman; J.K. Elliott - For: Crown Zellerbach Corp. - April 17, 1943 - C.S. File 52/91

Found 70" Spruce. Alders missing.
Reset corner with 1½" I.P. and 3"x3"x6 ft. Spruce post, from which
Orig. 70" Spruce S.21°W., 34.32 ft. to nail "S10 T21S R12W BT".
5" Spruce N.19°E., 45.7 ft. to nail, crayon mkd. "RP BT".

Survey by Richard J. Hintz - For: Champion International and International Paper Co. - March 1980 - M 79-30 and C.S. File 58/140

Found orig. 70" Spruce BT, stump, with nail in face.
Set 2" I.P. with stamped brass cap, from which
16" Spruce bears N.14°30'E., 51.7 ft., scribed.
70" Spruce stump bears N.21°00'E., (not S.21°W. as per notes) 34.3 ft. Orig. BT.
50" Spruce uproot, bears S.31°45'E., 20.6 ft. to a R.R. Spike driven in the upper quarter.
12" Spruce bears S.35°00'W., 69.3 ft., scribed.
8" Spruce bears N.9°00'W., 47.7 ft., scribed.
The 1½" I.P., post and 5" Spruce BT as per 1943 were gone.

Found OK by C. Mulkins, July 1997 - M 127-39