

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1276)

Set qr. sec. post, from which
A yellow-wood, 5" dia., bears N.70°W., 12 lks.
A fir, 36" dia., bears S.89°E., 100 lks.

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch
- April 29, 2013 - C.S. File 67/38-28 & M165-36

A search was made for original BTs; no evidence.
Corner set by survey in M165-36
Set - A 2½" dia. brass cap on a 1" I.D. by 30" long iron pipe
is set plumb in ground and protruding 4" above
surface. (Cap mkd.)

DOUGLAS COUNTY SURVEYOR

T21S

R12W

¼ S 26
S 35

2013

A 33" dia. D.Fir scribed "¼ S35 CS" "BT" on a double
blaze; bears S.39¾°E., 26.0 ft.

A 10" dia., power pole marked "AE 263"; bears S.34½°W.,
70.8 ft. 24

A 24" dia., D.Fir scribed "¼ S26 CS" "BT" on a double
blaze; bears N.89¼°W., 36.3 ft.

An 8½" dia. power pole marked "AE 263"; bears N.16¾°W.,
12.5 ft. 23

Note- BC monument is at most easterly summit of main E'ly -
W'ly running spine ridge of Bolon Island. A lower &
smaller ridge runs NE from this location. Ridge is
covered with open woods composed of Alder, Fir, &
Cedar.

Compass decl. 15¾°E.